

Polar Version for Cold Rooms

- GlassGuard BlackBand® Protected to BS EN61549 Standard
- Up to 60% Higher Output at Lower Temperatures
- 5 Year Polar Lamp Technology
- No Sleeves or Diffusers Necessary
- Quick & Easy Lamp Replacement
- Low Investment Compared With LED
- Passes All Hygiene Audits

Performance Data

Ambient Temp	Lumen Output
- 5° C	100%
- 15° C	90%
- 25° C	60%


T5 H.F With GlassGuard BlackBand®

Stock Code	Description
PRO28THF	Twin 28w T5
PRO54THF	Twin 54w T5
PRO35THF	Twin 35w T5
PRO49THF	Twin 49w T5
PRO80THF	Twin 80w T5

T8 H.F With GlassGuard BlackBand®

Stock Code	Description
PRO32THF	Twin 32w Watt-Miser T8
PRO36THF	Twin 36w T8
PRO58THF	Twin 58w T8
PRO51THF	Twin 51w Watt-Miser T8
PRO58THFXTM-POL	Twin 58w T8 Polar

Distributed By:-



Fotolec Technologies Ltd
5 Baird Way, Fison Way Industrial Estate
Thetford, Norfolk IP24 1JA

T: 01842 763752 • F: 01842 765252
E: sales@glassguard.co.uk • www.glassguard.co.uk

ARK3



BlackBand® to BS EN61549

IP65

THE ULTIMATE LOW MAINTENANCE



FOOD INDUSTRY LUMINAIRE

IP65 Fluorescent Luminaires

IP 65





- IP65 rated
- GlassGuard BlackBand® protected to BS EN61549 standard
- Low maintenance (no diffusers necessary)
- H.F control gear (5 year service life)
- Up to 40% energy saving with T5 lamps
- Fast payback on investment
- Food industry compliant



GlassGuard® IP65

Fully IP65 rated available in twin or single batten

H.F or low loss control gear available



24 Hour protection with GlassGuard BlackBand® Shatterproof Lamps
Manufactured to BS EN61549 standard

Low maintenance costs as no diffuser or clips necessary

Save up to 40% energy with T5 lamps!